

Diana

Table

Technical file



STACKABLE



SPARE PARTS



RECYCLABLE

Description

Frame

Manufactured with a 2 mm thick 6063-20 aluminum alloy profile.

Screws

Manufactured in AISI 304 stainless steel that offers great resistance to corrosion in marine environments.

Paint

Powder paint based on polyester resins that offers great resistance to light and outdoor environments in accordance with QUALICOAT international specifications and ISO-2409 and ISO-2360 regulations.

Accessories

Caps, studs and regulators made of polypropylene resin resistant to UV rays.


Tabletop

HPL compact board formed by 10 mm thick resins.

Diana

Table

Capacity



A

C

A - 47,5 cm
B - 35,5 cm

C - 58 cm
D - 35,5 cm

3,6 kg

| Package | Units | Measures | Weight | Volume |
|---------|-------|----------------|---------|---------------------|
| Pallet | 12 u. | 60x49,5x190 cm | 47,7 kg | 0,56 m ³ |

| Loading capacity | Mega trailer | Cont. 20' | Cont. 40' | Cont. 40' High Cube |
|------------------|--------------|-----------|-----------|---------------------|
| Diana | 1.836 u. | 540 u. | 1.200 u. | 1.360 u. |

Finishes

Frame

Matte texture



White Aluminum Turtledove

Tabletop

HPL Basic



White Grey

HPL GD



Prado Moonwalk Skyline



Diana

Table

Maintenance plan

Weekly

Visual check of the general condition, removing dirt and ensuring there are no broken parts or damage that could be a danger to users.

Monthly

Check that the aluminum structure has no damage or deep scratches.
Check the structural strength and stability.
Check the condition of the caps and studs.

Annual

Repair any damage to the paint.
Replace any worn or damaged parts.

Wintering and storage

Clean with soapy water and a soft cloth.
Remove damp stains, sand and seawater.
Store vertically in a dry place in stacks of 10 units.

Observations

- Always use Balliu spare parts.
- Balliu does not manufacture parts for other brands.
- If the product is subject to heavy use, maintenance checks must be carried out more frequently.
- Do not use the product until maintenance is completed.
- Do not use aggressive chemicals to clean the product.
- Always use products with a neutral pH.
- Use a soft cloth to clean the product.

